

FB5X FOAM MAKING BRANCHPIPE

Features

- Light compact self inducing high output branchpipe
- Adjustable for 3% or 6% induction or premix solution operation
- Simple, water shut-off valve
- Wide operating pressure range
- Long range jet



General Description

The FB5X is a lightweight, easy to handle foam making branchpipe ideal for Fire Brigade first line appliances and general industrial use. It will operate from a water supply of 230 l/min. at 5.5 bar to produce approximately 2270 l/min. of foam, whilst inducing 3% or 6% foam liquid via a 3M long piercer pick up tube which can be supplied with the branchpipe. The branchpipe incorporates a water shut-off valve and an easily adjustable concentration control valve enabling 6% or 3% induction rates or premix operation to be selected. The unit is versatile but simple to operate and maintain.

Technical Information

Coupling

Handle

Water Requirement Operating pressure range	230 l/min. at 5.5 bar (50 gal/min at 80 lbf/in ²⁾ 3 to 10.5 bar (45 to 150 lbf/in2)
Foam Liquid Foam Liquid Consumption	P, F, FFFP, AFFF AR & S
with 3% liquid	7 l/min (1.5 gal/min
with 6% liquid	14 l/min (3 gal/min)
Foam Output	2270 l/min (500 gal/min)
Jet length	, (222
Bulk	21 m (70 ft)
Maximum	24 m (80 ft)
Coupling	,
Inlet	65 mm (2.5 in) (M)
	instantaneous
Foam pickup	20 mm (0.75in) quick
	release
Material	Light alloy
Weight	2 kg
Finish	
Foam tube and body	Epoxy polyester orange

Note: Performance figures are based on equipment using appropriate foam liquid with clean water 15 C (59 F) at an atmospheric pressure of 1 bar (14.5 lbf/in.²)

Anodised

Epoxy polyester black

Ordering Information

UL Listed Model	65 mm (2.5 in) instantar 3% or 6% or premix	
FB5X	65mm (2.5 in.) instantar 3% or 6% or premix	
FB5X MOD (N)	65mm (2.5 in) Instantaneous (M) Fixed at 6% 51 105 03	
FB5X	65mm (2.5 in) BSP (F) 3% or 6% premix	51 105 04
FB5X	65mm (2.5 in) Instantan Premix	eous (M) 51 105 02
ASSOCIATED EQUIPMENT		
Piercer pick-up tube 3M (10ft) long 54 109 0		54 109 00