

EXCEL 2000 HIGH EXPANSION FOAM GENERATOR



- **Lightweight**
- **High Output**
- **Easily Portable**
- **Water Turbine Powered**
- **By Pass System**
- **Built in Foam Induction System**
- **Smoke Extraction Option**

GENERAL SPECIFICATION

The Excel 2000 is a lightweight High Expansion Foam Generator powered by a water turbine and capable of producing very large volumes of High Expansion Foam with the minimum of operational difficulty. The Excel 2000 has its own built in foam induction system and thus only requires a pressurised water supply and synthetic foam concentrate supply to operate.

An additional feature is a water by pass system which permits control of the expansion rate allowing performance to be maintained at high back pressures. The Excel 2000 is capable of ducting foam to heights in excess of 15 metres.

APPLICATIONS

The Excel 2000 is designed for all High Expansion total flood applications such as found in warehouses, ships holds, cable ducting, machinery spaces etc. Water damage is minimised through expanding foam between five hundred and one thousand times with air, producing effective and rapid extinction. Increasing concern for the environment has resulted in the fixed version replacing Halon Gas in certain specialist installations including computer suites and electronic data processing areas. The Excel 2000 is powered by a water driven turbine making it ideal for use in hazardous areas such as found in chemical process plants and mines. Many specialised applications also exist such as the vapour suppression of Hazardous Material spills, blanketing LNG spill fires and tank inerting.

CONSTRUCTION

Manufactured with an International Orange glass reinforced fibre case, corrosion resistant pipework and fittings with an LG2 gunmetal maintenance free turbine and all nylon foam net. Each unit is supplied with 30 metres of expandable polythene for ducting foam.

PERFORMANCE

By-Pass Control	Water Pressure Bars	Total Water L/Min	By-Pass Flow L/Min	Flow to Nozzles L/Min	Foam Prod. M/Min	Foam Expansion
Open	4	205	60	145	100	750
	7	285	90	195	156	to
	10	330	105	225	220	1200
By-Pass Closed	4	190	nil	190	85	450
	7	260	nil	260	145	to
	10	310	nil	310	200	850

Note: Pressures are measured at the water inlet. Performance may vary according to ambient temperature and foam concentrate used.

OPTIONS

SMOKE EXTRACTION UNIT

Dual purpose version identical to the standard unit but with the added capacity of extraction of smoke at 285m³/min. A 7.5 metre length of smoke extraction ducting is supplied with this unit.

WHEELED VERSION

Both the standard and smoke extraction units can be supplied as wheeled versions enabling easy one man transportation. Two wheels are permanently fixed to one end of the body with a handle at the other. These wheels lock off the ground during use for complete stability.

DIMENSIONS AND WEIGHT

WIDTH 910MM HEIGHT 920MM DEPTH 480MM WEIGHT 54KG

SHIPPING SPECIFICATION

One Case: 1000 x 1000 x 600mm

Nett Weight: 54 Kg

Gross Weight: 74 Kg