

DF 130 MOBILE FOAM UNIT



- 130 litre capacity
- Suitable for all types of foam
- Highly mobile
- One man operation
- Long running times
- High capacity foam station for major risks

GENERAL SPECIFICATION

The DF 130 Mobile Foam Unit is ergonomically designed for rapid one man deployment ideal for protecting oil storage and loading terminals, paint and solvent stores, boiler engines rooms and other high risk areas. The unit only requires connection to a suitable pressurised water supply and filled with 3% foam concentrate will give running times in excess of 20 minutes with a total foam output of 2600 cubic metres.

CONSTRUCTION

- FOAM TANK** : 130L Capacity Chemically Resistant Internationally Orange GRP tank suitable for all foam types including Synthetics, Protein, Fluoroprotein, AFFF, FFFP and Alcohol Resistant types.
- CHASSIS** : Corrosion Resistant Plastic coated steel frame. Optional Stainless Steel chassis for marine applications.
- WHEELS** : Solid Rubber 400mm diameter.
- STANDARD FITTINGS** : Z225 Variable Inline Foam Inductor with On/Off ball valve on inlet.
- : HV225 Low Expansion Foam Branchpipe.
- : 2 x 15 metre x 45mm Fire Hoses fitted with Light Alloy Instantaneous Couplings. All fittings in aluminium light alloy.
- DIMENSIONS** : Weight (empty) 70 Kg (Overall) 990mm x 910mm x 710mm