

FOCORED FIRE HOSE

GENERAL SPECIFICATION

General purpose layflat delivery Hose suitable for industrial and rural fire brigades, Marine use, general industrial, commercial and civil engineering applications and washdown purposes. The red elastomeric coating provides abrasion resistance.

FEATURES

**Construction**

100% Twill weave, circular woven polyester yarns with rubber lining, and red elastomeric coating.

Rot Proof

Soft rot proof polyester jacket, tough, flexible and easy to handle.

Lightweight

Smooth, seamless, lightweight synthetic rubber lining, age resistant.

Approvals

Focored fully meets the requirements of the U.K. Home Office Specification JCDD 1/1 and British Standard BS6391:1983 for Type 1 hose, U.K. DOT - MSA (Marine Safety Approved) for Marine Use.

TECHNICAL DATA

Internal Diameter	mm	38	45	52	64	70	75	100
	inches	1 1/2"	1 3/4"	2"	2 1/2"	2 3/4"	3"	4"
Short Length Burst Pressure	bar	45	45	45	45	45	45	36
Maximum Use Pressure	bar	15	15	15	15	15	15	15

SHIPPING SPECIFICATION

Internal Diameter	mm	38	45	52	64	70	75	100
	inches	1 1/2"	1 3/4"	2"	2 1/2"	2 3/4"	3"	4"
Coil Diameter (25 metres)	cms	38	39	41	43	44	46	50
Weight	gm/M	240	250	315	365	440	555	690