

FOCOWHITE FIRE HOSE

GENERAL SPECIFICATION

General purpose layflat delivery Hose suitable for industrial and rural fire brigades, Marine use, general industrial, commercial and civil engineering applications and washdown purposes.

FEATURES



Construction	100% Twill weave, circular woven polyester yarns with rubber lining.
Rot Proof	Soft rot proof polyester jacket, tough, flexible and easy to handle.
Lightweight	Smooth, seamless, lightweight synthetic rubber lining, age resistant.
Approvals	Focowhite fully meets the requirements of the U.K. Home Office Specification JCDD 1/1 and British Standard BS6391:1983 for Type 1 hose, U.K. DOT - MSA (Marine Safety Approved) for Marine Use.

TECHNICAL DATA

Internal Diameter	mm	38	45	52	64	70	75	100
	inches	1 1/2"	1 3/4"	2"	2 1/2"	2 3/4"	3"	4"
Short Length Burst Pressure	bar	40	40	40	40	40	40	30
Maximum Use Pressure	bar	20	20	20	20	20	20	15

SHIPPING SPECIFICATION

Internal Diameter	mm	38	45	52	64	70	75	100
	inches	1 1/2"	1 3/4"	2"	2 1/2"	2 3/4"	3"	4"
Coil Diameter (25 metres)	cms	38	39	41	43	44	46	50
Weight	gm/M	180	230	270	360	430	460	630