

# CO<sup>2</sup> MOBILE UNITS

The Norfolk CO2 wheeled extinguisher is used on Class B (flammable liquid) fires. It is also safe to be used on live electrical fires.

Typically used to protect::

- The food industry
- Electrical control rooms
- Power stations
- Ship's engine rooms
- Computer installations

The extinguishers are available in a variety of sizes



Norfolk Range Wheeled CO2 Extinguishers			
Extinguisher code	NWC10	NWC20	NWC30
Propellant type	Stored pressure		
Extinguishant	Carbon Dioxide CO2		
Capacity	10kg	20kg	30kg
Paint finish/colour	Red (RAL 3000)		
Fire class	B Type		
Discharge hose	6 metre Hose & Horn with control valve		
Operating temperature	-20°C to +60°C		
Test pressure	250 bar		
Operating pressure @ 20°C	50 Bar		
Ave. discharge duration	22 secs	44 secs	68 secs
Discharge range	4 metres		
Safe operating distance	2 metres		
Electrical	Suitable for use on live electrical equipment up to 1000v at a distance of 1m		
Cylinder	Steel		
Height	117cm	129cm	149cm
Width	44cm	44cm	44cm
Depth	42cm	42cm	42cm
Full weight	49kg	82kg	105kg
Empty weight	39kg	62kg	75kg
Wheel diameter	300mm	300mm	300mm
Approvals – EN 1866	✓	✓	✓

## Helilance

A CO2 lance is available and is used extensively at airports and offshore installations world wide.

Its design has been specifically aimed at protecting helicopters and aircraft engines.

