

## ATTACK SELECT FLOW BRANCHPIPES

### FEATURES



#### SELECTABLE FLOW RANGE (AT 6 BAR)

Attack 100 = 75, 100, 125 & 230 L/Min (Alternative Flows Available)

Attack 500 = 125, 250, 375 & 500 L/Min

Attack 750 = 285, 460, 600 & 750 L/Min

Cohesive jet and dense water spray pattern at each flow setting.

Normal operating range 5 to 8 bar, but fully operational at pressures as low as 3.5 bar

#### POWERFUL FOG PATTERN - STAINLESS STEEL SPINNING TEETH

Computer designed stainless steel turbine spinning teeth produce an extremely dense fog pattern, giving excellent fire fighting capability and higher degrees of personal protection. Plastic teeth are available as a lower cost option.

#### NARROW ANGLE CLICK SETTING

The branch jet/spray pattern has a single narrow angle click position, which is positive enough to hold the setting in operational use and is easily identifiable in 'blind' fire scenarios.

#### LOW MAINTENANCE AND RUGGED CONSTRUCTION

The stainless steel ball valve design means only minimal maintenance. A stainless steel mesh filter and wide flush setting stop any obstruction of the water flow in use.

A gunmetal version is also available.

### SPECIFICATION

Model Ref	Description	Length
A100-19 A100-25	Branch With ¾" or 1" BSP Female Swivel Inlet	230 mm
A500-65	Branch With 2½" Male instantaneous Swivel Inlet	325 mm
A750-65	Nozzle With 2½" Male Instantaneous Swivel Inlet	340 mm

Weight: Attack 100 - 1.6kg, Attack 500 – 1.8kg, Attack 750 - 2.4kg

Main Body/Barrel: Hard Anodised Aluminum

Ball Valve: Stainless Steel

Front Bumper: Shockproof Polyurethane